

400 SERIES

Model Number	Door Trim Color	Fireplace Interior Opening				Shroud Exterior Dimensions
		Height min	Height max	Width min	Width max	
2943-400	Cast Iron with Solid Brass Trim	22.5"	27"	32"	39"	29" x 43"
2948-400		22.5"	27"	36"	44"	29" x 48"
3348-400		22.5"	31"	36"	44"	33" x 48"
Special Order		Custom		Custom		Custom

SPECS

FEATURES

Etching	Air Wash	Fits Models	Rotary Air Control
Forest Scene	Standard	Smart Fireplaces 33 & 37	Standard
Forest Scene	Standard	Smart Fireplaces 37 & 42	Standard
Forest Scene	Standard	Smart Fireplaces 37 & 42	Standard
Forest Scene	Standard	Most Masonry Fireplaces	Standard


500 SERIES

Model Number	Door Color	Fireplace Interior Opening				Shroud Exterior Dimensions
		Height min	Height max	Width min	Width max	
2943-500A	Cast Iron	22.5"	27"	32"	39"	29" x 43"
2948-501A		22.5"	27"	36"	44"	29" x 48"
3348-502A		22.5"	31"	36"	44"	33" x 48"
2943G-500A	24K Gold	22.5"	27"	32"	39"	29" x 43"
2948G-501A		22.5"	27"	36"	44"	29" x 48"
3348G-502A		22.5"	31"	36"	44"	33" x 48"
2943N-500A	Brushed Nickel	22.5"	27"	32"	39"	29" x 43"
2948N-501A		22.5"	27"	36"	44"	29" x 48"
3348N-502A		22.5"	31"	36"	44"	33" x 48"
Special Order	Choice	Custom		Custom		Custom

SPECS

FEATURES

Etching	Air Wash	Fits Models	Easy Touch Air Control
None	Standard	Smart Fireplaces 33 & 37	Standard
None	Standard	Smart Fireplaces 37 & 42	Standard
None	Standard	Smart Fireplaces 37 & 42	Standard
Wheat Pattern	Standard	Smart Fireplaces 33 & 37	Standard
Wheat Pattern	Standard	Smart Fireplaces 37 & 42	Standard
Wheat Pattern	Standard	Smart Fireplaces 37 & 42	Standard
None	Standard	Smart Fireplaces 33 & 37	Standard
None	Standard	Smart Fireplaces 37 & 42	Standard
None	Standard	Smart Fireplaces 37 & 42	Standard
Choice	Standard	Most Masonry Fireplaces	Standard



FAQ

With included hardware, doors install easily and quickly for secure, airtight performance.

Q. How much will Country Flame fireplace doors heat?

A. They are rated at 35,000 BTUs per hour.

Q. Can the doors be installed on masonry fireplaces?

A. Yes. On either masonry fireplaces or the Country Flame fireplace furnace, they increase burn times and provide much more heat than conventional doors.

Q. Can they be installed over rough stone facing?

A. Yes. Fill voids behind frame with insulation or cement.

Q. How long will the doors last?

A. Under normal use, the 1/4" plate steel frame and heavy cast-iron doors should last a lifetime.

Q. Will they hold a fire longer?

A. This airtight system offers the same type of control as high-quality stoves and inserts. Many users report fires that burn overnight.

Q. How do I control the fire?

A. Use the rotary air control on the 400 series and the concealed easy-touch air control on the 500 series for precise regulation.

Q. Are there restrictions on the use of these doors?

A. Yes. They cannot be installed over zero-clearance fireplaces.

Universal Doors



Add efficiency, safety, and beauty to your existing fireplace with heavy-duty Country Flame Universal Fireplace Doors. Stop the loss of heat up a drafty, open fireplace flue. Radiant heat from the heavy, quarter-inch steel surround, the high-temperature ceramic glass, and the heavy-duty door frames means high BTU output.



150 Michigan St. S.E., Hutchinson, MN 55350
Phone: (800) 495-3196 Fax: (320) 587-8872
information@magnumheat.com
www.countryflame.com



by American Energy Systems Inc.



500 Series Door features your choice of three finishes: Black, Gold, or Brushed Nickel.

400 SERIES

- Large viewing area with etched glass
- High-temperature ceramic windows
- Air wash (helps keep glass clean)
- Positive-seal airtight design
- High BTU radiant output
- Wooden door handles
- Factory-cured high-temperature satin finish on door surrounds
- Rotary air control
- Solid brass door trim

ADJUSTABLE HINGES



ROTARY AIR CONTROL

SOLID BRASS DOOR TRIM

500 SERIES

- Large viewing area
- Etched glass (with gold only)
- High-temperature ceramic windows
- Air wash (helps keep glass clean)
- Positive-seal airtight design
- High BTU radiant output
- “Stay-cool” coil handles
- Factory-cured high-temperature satin finish on door surrounds
- Easy-touch air control
- Door frames available in Black, 24K Gold, or Brushed Nickel

WHEAT ETCHING (gold only)

EASY TOUCH AIR CONTROL



ADJUSTABLE HINGES